

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)


PCT

(10) International Publication Number
WO 2005/060863 A1

- (51) International Patent Classification⁷: **A61C 8/00** (74) Agent: **OLSSON, Gunnar**; Nobel Biocare AB (publ), P.O. Box 5190, S-402 26 Göteborg (SE).
- (21) International Application Number: PCT/SE2004/001917 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 20 December 2004 (20.12.2004) (81) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0303460-0 22 December 2003 (22.12.2003) SE
- (71) Applicant (for all designated States except US): **NOBEL BIO CARE AB (PUBL.)** [SE/SE]; Box 5190, S-402 26 Göteborg (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **JÖRNEUS, Lars** [SE/SE]; Riabergsvägen 7B, S-430 30 Frillesås (SE). **DURIC, Sanel** [SE/SE]; c/o Lundgren, Odingsgatan 22B, S-411 03 (SE).

[Continued on next page]

(54) Title: IMPLANT



(57) Abstract: An implant (5) can be fitted in an implantation site in a hole (4) formed in a jaw bone (1) where it is exposed to an impinging force or impinging forces (F1, F2). The implant can comprise one or more peripherally extending surfaces (5d) which are arranged at its upper/outer portion (5b) and which can be placed against a jaw bone part (3) at the outlet opening (4b) of the hole. Each surface (5d) is provided with a pattern (8) of grooves and/or recesses. Some of these are designed so that, in the implantation site, they extend substantially at right angles to, and if appropriate parallel to, said forces (F1, F2) when these assume principal directions differing from the longitudinal direction (5c) of the implant. By virtue of this arrangement, it is possible to achieve effective load-bearing in different implantation situations.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.